


泉州豐群電子有限公司

C.C. FENG CHIUN ELECTRONIC CO., LTD.

OFFICE: TEL:+886-2-82522781
FAX:+886-2-82522782

FACTORY: TEL:+86-595-22632579
FAX:+86-595-22632580

1	MODEL	40BOX-05(GP)
2	Dimension	100.0X45.0X20.5H Weight 50.5 Gram.
3	Magnet	Materials Rare Earth Size $\varnothing 15.5 \times 2.0$ mm. $\varnothing 15.5 \times 4.0$
4	Nominal Impedance	8 Ohm $\pm 15\%$
5	Power Rating	Normal 5.0 W. Maximum 7.0 W.
6	Lowest Resonant Frequency	360 \pm 72 Hz
7	Output Sound Pressure Level	87 \pm 3 dB / 1 Watt 1 Meter.
		Average at 500,600,800,1000 Hz
8	Frequency Range	280~20K Hz. Average SPL-10 dB.
9	Distortion	5 % Maximum At 1000 Hz 1.0 W.
10	Abnormal Sound Test	Must be Normally Tested By 6.32 Volts Sine Wave.
11	Load Test	White Noise with Weighted Filter 6.32 Volts. (RMS) 96 Hrs.
12	Operation Temperature	-25°C ~ +70°C
13	Storage Temperature	-40°C ~ +85°C
14	Polarity	Diaphragm shall move Forward when Apply a Positive DC
		Current to the "+" or "Marked" Terminal.
15	Remarks	Above specifications on the strength of CNS4784 and CNS4785.



Dimension:
details see drawing name “40BOX-05(GP)外观图”。

Admitted:

Approved:

Made: